
Automatic controller for light controlling system

Flush Mounted Inserts

Tyyppi: 2116/11 UC-916-510

Tuotekoodi: 2CKA006599A3047

GTIN: 4011395316269



For DALI broadcast service (via central telegram). With integrated DALI power adaptor. For switching and dimming up to 64 DALI- devices like electronic ballasts and transformers with DALI-interface. With rotary control and ON/OFF push operation. For changing the colour temperature of >tunable white< lamps, which meet DALI Standard IEC 62386-209 (Device Type 8). Colour temperature can then be set between 2,700 K - 6,500 K. With electronic short-circuit protection. With electronic overload protection. Brightness power-on level and background brightness level adjustable, buffered. With integrated LED illumination for orientation. Color of orientation light adjustable (18 presets and OFF). Up to 5 potentiometers are connectable in parallel. Up to 3 potentiometers are connectable in parallel in active mode. Not suitable for combining with other DALI sensors or central units of other manufacturers. DALI-voltage: 15,5 V= Rated current: max. 75 mA Power consumption: < 2,5 W Number of DALI-units: 37 in case of one active power-potentiometer in case of three active power-potentiometer in parallel connection: 111 Active mode: the potentiometer is supporting the necessary control circuit for other DALI-devices. Passive mode: the potentiometer is suitable as additional operation point. Max. DALI-cable length: 300 m (1,5 - 2,5 mm²). Without cover plate.

Tekniset tiedot

Sähkösuureet

| | |
|------------------|-------|
| Nominal voltage: | 230 V |
|------------------|-------|

Pakkaus

| | |
|----------|-----|
| Paketti: | 1/1 |
| Yksikkö: | kpl |

ETIM Data

| | |
|--|-------------------------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000534 |
| Mounting method: | Flush mounted (plaster) |
| Rated current: | 0.08 A |
| Method of operation: | Turn/push button |
| Min. depth of built-in installation box: | 28.5 mm |
| Device width: | 71 mm |
| Device height: | 71 mm |
| Device depth: | 53.8 mm |
| Metallic colour: | Ei |
| Compatible with Apple HomeKit: | Ei |
| Compatible with Google Assistant: | Ei |
| Compatible with Amazon Alexa: | Ei |
| IFTTT support available: | Ei |