

Tuotekortti

Euro socket outlet, Impressivo, 3-gang, shuttered, screwless terminals, branching terminals, white



Socket outlet

Euro socket outlet, Impressivo, 3-gang, shuttered, screwless terminals, branching terminals, white



Tyyppi: 303UC-84

Tuotekoodi: 2TKA00000433

GTIN: 6438199001593



3-gang Euro socket outlet with center plate. There are terminals for each contact of the socket outlet for max 4 rigid wires and 2 X-terminals for 2-rigid wires. The socket outlet insert without the cover plate is screen-protected.

Tekniset tiedot

Sähkösuureet

Nominal current:	2.5 A
Nominal voltage:	250 V

Luokitus

Suitable for degree of protection (IP):	IP21
---	------

Pakkaus

Paketti:	1/10/100/1800
Yksikkö:	kpl

ETIM Data

© ABB 2026

Y-tunnus 0763403-0

www.installationmaterials.com

Asiakaspalvelukeskus

puh. 010 222 1999

contact.center@fi.abb.com

Puhelinvaihte

010 22 11

Tuotekortti

Euro socket outlet, Impressivo, 3-gang, shuttered, screwless terminals, branching terminals, white



ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Model:	EURO plug (CEE 7/16)
Number of active pins (round):	2
With signal lamp:	Ei
Number of units:	3
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Ei
With enhanced contact protection:	Kyllä
Label space/information surface:	Ei
Colour:	White
RAL-number (similar):	9016
Metallic colour:	Ei
Transparent:	Ei
Lockable:	Ei
Eject-mechanism:	Ei
Insulated mounting:	Ei
With function lighting:	Ei
With orientation lighting:	Ei
Over voltage protection:	Ei
Fault current protection:	Ei
With miniature fuse:	Ei
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Untreated
Surface finishing:	Glossy
Anti-bacterial treatment:	Ei

Tuotekortti

Euro socket outlet, Impressivo, 3-gang, shuttered, screwless terminals, branching terminals, white



With loop through function:	Ei
With on/off switch:	Ei
Rotated central insert:	Ei
Frequency:	50 Hz
Device width:	71 mm
Device height:	35 mm
Device depth:	71 mm
Min. depth of built-in installation box:	23 mm