

Socket outlet

Socket outlet, Impressivo, Schuko, 1-gang, shuttered, screwless terminals, anthracite



Tyyppi: 20EUJ-81

Tuotekoodi: 2TKA00000438

GTIN: 6438199001487



There are terminals for each contact of the socket outlet. No 2 X-terminals. The terminals are for max 2 rigid wires.

Tekniset tiedot

Sähkösuureet

| | |
|------------------|-------|
| Nominal current: | 16 A |
| Nominal voltage: | 250 V |

Luokitus

| | |
|---|------|
| Suitable for degree of protection (IP): | IP21 |
| Protection class: | IP21 |

Pakkaus

| | |
|----------|---------------|
| Paketti: | 1/10/100/1200 |
| Yksikkö: | kpl |

ETIM Data

| | |
|---------------|----------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000125 |

| | |
|-----------------------------------|------------------------------|
| Number of active pins (round): | 2 |
| With signal lamp: | Ei |
| Number of units: | 1 |
| Number of phases: | 1 |
| Imprint/indication: | None |
| Connection type: | Push-in clamp |
| With hinged lid: | Ei |
| With enhanced contact protection: | Kyllä |
| Label space/information surface: | Ei |
| Colour: | Anthracite |
| RAL-number (similar): | 7021 |
| Metallic colour: | Ei |
| Transparent: | Ei |
| Lockable: | Ei |
| Eject-mechanism: | Ei |
| Insulated mounting: | Ei |
| With function lighting: | Ei |
| With orientation lighting: | Ei |
| Over voltage protection: | Ei |
| Fault current protection: | Ei |
| With miniature fuse: | Ei |
| Special power supply: | No special power supply |
| Mounting method: | Flush mounted (plaster) |
| Type of fastening: | Mounting with claw and screw |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Kyllä |
| Surface protection: | Untreated |
| Surface finishing: | Glossy |
| Anti-bacterial treatment: | Ei |
| With loop through function: | Ei |
| With on/off switch: | Ei |
| Rotated central insert: | Ei |
| Frequency: | 50 Hz |

Tuotekortti

Socket outlet, Impressivo, Schuko, 1-gang, shuttered, screwless terminals, anthracite



| | |
|--|-------|
| Device width: | 85 mm |
| Device height: | 45 mm |
| Device depth: | 85 mm |
| Min. depth of built-in installation box: | 28 mm |