

Socket outlet

Socket outlet, ProDuct, 2xShuko, white

Tyyppi: AUD10-214**Tuotekoodi:** 2TKA00000809**GTIN:** 6438199002019

The socket-outlet is approved for extending a branch circuit with solid and rigid wires. When chaining several AUD10-socket-outlets, the recommended length of intermediate cables is 120 mm. The end piece package AUD30 or AUD31 is required for each socket group. The depth of box is 45 mm.

Tekniset tiedot

Sähkösuureet

| | |
|------------------|-------|
| Nominal current: | 16 A |
| Nominal voltage: | 250 V |

Luokitus

| | |
|---|------|
| Suitable for degree of protection (IP): | IP20 |
|---|------|

Pakkaus

| | |
|----------|--------|
| Paketti: | 10/100 |
| Yksikkö: | kpl |

ETIM Data

| | |
|---------------|----------|
| ETIM Version: | ETIM-9.0 |
|---------------|----------|

| | |
|-----------------------------------|----------------------------|
| ETIM Class: | EC000125 |
| Number of active pins (round): | 2 |
| With signal lamp: | Ei |
| Number of units: | 2 |
| Number of phases: | 1 |
| Imprint/indication: | None |
| Connection type: | Push-in clamp |
| With hinged lid: | Ei |
| With enhanced contact protection: | Kyllä |
| Label space/information surface: | Ei |
| Colour: | White |
| RAL-number (similar): | 9010 |
| Metallic colour: | Ei |
| Transparent: | Ei |
| Lockable: | Ei |
| Eject-mechanism: | Ei |
| Insulated mounting: | Ei |
| With function lighting: | Ei |
| With orientation lighting: | Ei |
| Over voltage protection: | Ei |
| Fault current protection: | Ei |
| With miniature fuse: | Ei |
| Special power supply: | No special power supply |
| Mounting method: | Wall duct |
| Type of fastening: | Snap mounting (engagement) |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Kyllä |
| Surface protection: | Untreated |
| Surface finishing: | Matt |
| Anti-bacterial treatment: | Ei |
| With loop through function: | Ei |
| With on/off switch: | Ei |
| Rotated central insert: | Ei |

Tuotekortti

Socket outlet, ProDuct, 2xShuko, white



| | |
|----------------|-------|
| Frequency: | 50 Hz |
| Device width: | 45 mm |
| Device height: | 85 mm |
| Device depth: | 80 mm |