

# Socket outlet

Socket outlet, ProDuct, 2xShuko, white

**Tyyppi:** AUD10-214

**Tuotekoodi:** 2TKA00000809

**GTIN:** 6438199002019



The socket-outlet is approved for extending a branch circuit with solid and rigid wires. When chaining several AUD10-socket-outlets, the recommended length of intermediate cables is 120 mm. The end piece package AUD30 or AUD31 is required for each socket group. The depth of box is 45 mm.

## Tekniset tiedot

### Sähkösuureet

Nominal current:	16 A
Nominal voltage:	250 V

### Luokitus

Suitable for degree of protection (IP):	IP20
---	------

### Pakkaus

Paketti:	10/100
Yksikkö:	kpl

### ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	Ei
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Ei
With enhanced contact protection:	Kyllä
Label space/information surface:	Ei
Colour:	White
RAL-number (similar):	9010
Metallic colour:	Ei
Transparent:	Ei
Lockable:	Ei
Eject-mechanism:	Ei
Insulated mounting:	Ei
With function lighting:	Ei
With orientation lighting:	Ei
Over voltage protection:	Ei
Fault current protection:	Ei
With miniature fuse:	Ei
Special power supply:	No special power supply
Mounting method:	Wall duct
Type of fastening:	Snap mounting (engagement)
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	Ei
With loop through function:	Ei
With on/off switch:	Ei
Rotated central insert:	Ei

# Tuotekortti

Socket outlet, ProDuct, 2xShuko, white



Frequency:	50 Hz
Device width:	45 mm
Device height:	85 mm
Device depth:	80 mm