

Countdown timer

Basic timer, Impressivo, aluminum

Tyyppi: T210-83**Tuotekoodi:** 2TKA00000877**GTIN:** 6438199002262

Fixed time options: 15min, 30min, 1h, 2h, 4h and 8h. Exchangeable labels with the time options to mark center plate with selected time. 230 VAC, 50Hz, 0 - 40C, IP21, 2-pole wiring. 10A resistiv load (2300W), 2AX-load (e.g. fluorescent lamp). Screw terminals max 2,5mm². Signal light when active.

Tekniset tiedot

Sähkösuureet

Nominal voltage:	230 V
Rated current:	10 A

Luokitus

Suitable for degree of protection (IP):	IP21
Protection class:	IP21

Thermal conditions

Operating temperature:	0 ... 40 °C
------------------------	-------------

Dimensions

A:	70 mm
B:	70 mm
C:	32 mm
Recessing dimensions:	18 mm

Electronics

Operating frequency:	50 Hz
Conductor size max.:	2,5 mm ²

Pakkaus

Paketti:	1/10/100/1200
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC001594
Assembly arrangement:	Basic element with central cover plate
Number of contacts as normally open contact:	1
Model:	Electronic
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Surface protection:	Untreated
Surface finishing:	Glossy
Colour:	Aluminium
RAL-number (similar):	9006
Transparent:	Ei
Shortest switching interval:	15 min
Random generator:	Ei
Astro program:	Ei

Tuotekortti

Basic timer, Impressivo, aluminum



Substation input:	Ei
Rated current:	10 A
With brightness sensor connection:	Ei
Max. power:	2300 W
Compatible with Apple HomeKit:	Ei
Compatible with Google Assistant:	Ei
Compatible with Amazon Alexa:	Ei
IFTTT support available:	Ei
Built-in depth:	18 mm
Min. depth of built-in installation box:	18 mm
Device width:	71 mm
Device height:	34 mm
Device depth:	71 mm