
Push button

Push button, 4/2-gang, Impressivo, aluminum

Tyyppi: FAP1204-83

Tuotekoodi: 2TKA00000914

GTIN: 6438199002293



4/2-gang push button panel to control bistable relays or electronic control systems. Load capacity 1A AC/DC. White LED-light with adjustable illumination. Installation on surface or on top of a standard flush mounting box.



Tekniset tiedot

Sähkösuureet

Nominal voltage:	24 V
Operating voltage:	5-24 V ac/dc

Luokitus

Suitable for degree of protection (IP):	IP20
---	------

Thermal conditions

Operating temperature:	5 ... 40 °C
------------------------	-------------

Signal products

Loading capacity of switch (max):	1 mA - 1 A ac/dc res. 5 - 24V ac/dc
Current drain of signal lamp:	10 mA ac/17 mA dc

Pakkaus

Paketti:	1/10/100/1200
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000029
Assembly arrangement:	Basic element with central cover plate
Model:	Group push button
Method of operation:	Push button
Number of contacts as normally closed contact:	4
Contactless type:	Ei
Number of rockers:	4
Number of poles:	1
Rated current:	1 A
With lighting:	Ei
Feedback-signal contact:	Kyllä
Connection type:	Screwed terminal
Mounting method:	Flush mounted (plaster)
Type of fastening:	Screw mounting
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Anti-bacterial treatment:	Ei
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	Aluminium
RAL-number (similar):	9006
Transparent:	Ei
Label space/information surface:	Ei
Imprint:	None
Impact strength:	IK00
Device width:	71 mm

Tuotekortti

Push button, 4/2-gang, Impressivo, aluminum



Device height:	71 mm
Device depth:	20 mm
Min. depth of built-in installation box:	21 mm
Compatible with Apple HomeKit:	Ei
Compatible with Google Assistant:	Ei
Compatible with Amazon Alexa:	Ei
IFTTT support available:	Ei