

Lighting outlet

DCL lighting outlet, wall outlet,
85x85mm, aluminum



Tyyppi: AKK6-83

Tuotekoodi: 2TKA00000935

GTIN: 6438199002354



DCL lighting outlet, wall outlet, 85x85mm, aluminum

Tekniset tiedot

Sähkösuureet

Nominal current:	6 A
Nominal voltage:	250 V

Luokitus

Suitable for degree of protection (IP):	IP20
---	------

Dimensions

Dimensions:	85x85x38 mm
-------------	-------------

Pakkaus

Paketti:	10/100
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Model:	DCL
With signal lamp:	Ei
Number of units:	1
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
With hinged lid:	Ei
With enhanced contact protection:	Ei
Label space/information surface:	Ei
Colour:	Aluminium
RAL-number (similar):	9006
Metallic colour:	Kyllä
Transparent:	Ei
Lockable:	Ei
Eject-mechanism:	Ei
Insulated mounting:	Ei
With function lighting:	Ei
With orientation lighting:	Ei
Over voltage protection:	Ei
Fault current protection:	Ei
With miniature fuse:	Ei
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Lacquered
Surface finishing:	Matt
Anti-bacterial treatment:	Ei
With loop through function:	Ei

Tuotekortti

DCL lighting outlet, wall outlet, 85x85mm, aluminum



With on/off switch:	Ei
Rotated central insert:	Ei
Frequency:	50...60 Hz
Impact strength:	IK00
Device width:	85 mm
Device height:	39 mm
Device depth:	85 mm
Min. depth of built-in installation box:	25 mm