

Junction box

Surface-mounted junction box, IP65, 86 x 86 mm, red



Tyyppi: AP9R

Tuotekoodi: 2TKA00001563

GTIN: 6438199003184



The square junction box AP9R (2,5 mm², 500 V) is equipped with 12 membrane cable entries (Ø 17 mm) in the sides, and two in the bottom. Cables are easy to connect by simply inserting the stripped ends through the inlets. The box locks by snapping and can be opened by inserting a screwdriver (for example) into the opening slots - no screws are needed. The box can be furnished with strain-reliefs AS9.10, AS9, AS9.1 and AS9.3. Fits up to Ø17 mm cable. VDE-approved. Mounting temperature -25...+60 °C. Made of halogen free material (IEC/61249-2-21).

Tekniset tiedot

Sähkösuureet

Rated voltage:	500 V
Wire range:	2.5 mm ²

Luokitus

Enclosure class:	IP65
------------------	------

Dimensions

Dimensions:	86x86x39 mm
Weight:	66 g

Thermal conditions

Operating temperature:	-25 ... 60 °C
------------------------	---------------

Colors

Colour:	Red
Colour code:	RAL3000

Pakkaus

Paketti:	5/50
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002600
Model:	Junction box
Equipped with:	None
Shape:	Square
Mounting method:	Universal
Mounting in the soil:	Ei
Mounting under water:	Ei
Inlet from the rear:	Kyllä
Length:	39 mm
Width:	86 mm
Depth:	86 mm
Tackable:	Ei
Number of inlets:	14
Type of housing feed-through:	Seal membrane
Material:	Plastic
Halogen free:	Kyllä
Surface protection:	Untreated
Colour:	Red
Degree of protection (IP):	IP65

Tuotekortti

Surface-mounted junction box, IP65, 86 x 86 mm, red



Cover model:	Blind cover
Transparent cover:	Ei
Cover attachment:	Snapped on
Castable:	Ei
With casting compound:	Ei
Sealable:	Kyllä
Rated insulation voltage Ui:	500 V
With screening:	Ei
Weatherproof:	Kyllä
Operating temperature:	-25...60 °C
Explosion-tested version:	Ei