

Socket outlet

Socket outlet, Impressivo, Schuko, 4-gang, shuttered, screwless terminals, anthracite



Tyyppi: 404EA-81

Tuotekoodi: 2TKA00001614

GTIN: 6438199003351



There is 2 times 2-gang socket outlet inserts in one unit. The socket outlet inserts are internally connected. In one socket outlet insert there are terminals for each contact of the socket outlet for max 4 rigid wires. No X-terminals.

Tekniset tiedot

Sähkösuureet

| | |
|------------------|-------|
| Nominal current: | 16 A |
| Nominal voltage: | 250 V |

Luokitus

| | |
|-----------------------------------------|------|
| Suitable for degree of protection (IP): | IP21 |
| Protection class: | IP21 |

Pakkaus

| | |
|----------|------|
| Paketti: | 1/20 |
| Yksikkö: | kpl |

ETIM Data

| | |
|-----------------------------------|---------------------------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000125 |
| Number of active pins (round): | 2 |
| With signal lamp: | Ei |
| Number of units: | 4 |
| Number of phases: | 1 |
| Imprint/indication: | None |
| Connection type: | Push-in clamp |
| With hinged lid: | Ei |
| With enhanced contact protection: | Kyllä |
| Label space/information surface: | Ei |
| Colour: | Anthracite |
| RAL-number (similar): | 7021 |
| Metallic colour: | Ei |
| Transparent: | Ei |
| Lockable: | Ei |
| Eject-mechanism: | Ei |
| Insulated mounting: | Ei |
| With function lighting: | Ei |
| With orientation lighting: | Ei |
| Over voltage protection: | Ei |
| Fault current protection: | Ei |
| With miniature fuse: | Ei |
| Special power supply: | No special power supply |
| Mounting method: | Surface mounted (plaster) |
| Type of fastening: | Mounting with screw |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Kyllä |
| Surface protection: | Untreated |
| Surface finishing: | Glossy |
| Anti-bacterial treatment: | Ei |

Tuotekortti

Socket outlet, Impressivo, Schuko, 4-gang, shuttered, screwless terminals, anthracite



| | |
|-----------------------------|--------|
| With loop through function: | Ei |
| With on/off switch: | Ei |
| Rotated central insert: | Ei |
| Frequency: | 50 Hz |
| Device width: | 115 mm |
| Device height: | 42 mm |
| Device depth: | 100 mm |