

Tuotekortti

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, aluminum



Socket outlet

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, aluminum



Tyyppi: 302EUJT-83

Tuotekoodi: 2TKA00002006

GTIN: 6438199003658



There are terminals for each contact of the socket outlet for max 4 rigid wires. No X-terminals. The socket outlet insert without the cover plate is screen-protected. Wery flat construction. Installatin in special 1,5X mounting box.

Tekniset tiedot

Sähkösuureet

Nominal current: 16 A

Nominal voltage: 250 V

Luokitus

Suitable for degree of protection (IP): IP21

Pakkaus

Paketti: 1/10/100/1200

Yksikkö: kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	Ei
Number of units:	2
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Ei
With enhanced contact protection:	Kyllä
Label space/information surface:	Ei
Colour:	Aluminium
RAL-number (similar):	9006
Metallic colour:	Kyllä
Transparent:	Ei
Lockable:	Ei
Eject-mechanism:	Ei
Insulated mounting:	Ei
With function lighting:	Ei
With orientation lighting:	Ei
Over voltage protection:	Ei
Fault current protection:	Ei
With miniature fuse:	Ei
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Lacquered
Surface finishing:	Matt

Tuotekortti

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, aluminum



Anti-bacterial treatment:	Ei
With loop through function:	Ei
With on/off switch:	Ei
Rotated central insert:	Ei
Frequency:	50 Hz
Device width:	80 mm
Device height:	40 mm
Device depth:	120 mm
Min. depth of built-in installation box:	28.5 mm