

# Socket outlet

Euro socket outlet, 3-gang, shuttered, screwless terminals, branching terminals, painted steel



**Tyyppi:** 303UC-866

**Tuotekoodi:** 2TKA00002905

**GTIN:** 6438199004617



3-gang Euro socket outlet with center plate. There are terminals for each contact of the socket outlet for max 4 rigid wires and 2 X-terminals for 2-rigid wires. The socket outlet insert without the cover plate is screen-protected.

## Tekniset tiedot

### Sähkösuureet

Nominal current:	2.5 A
Nominal voltage:	250 V

### Luokitus

Suitable for degree of protection (IP):	IP21
---	------

### Pakkaus

Paketti:	1/10/100/1800
Yksikkö:	kpl

### ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Model:	EURO plug (CEE 7/16)
Number of active pins (round):	2
With signal lamp:	Ei
Number of units:	3
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Ei
With enhanced contact protection:	Kyllä
Label space/information surface:	Ei
Colour:	Stainless steel
Metallic colour:	Kyllä
Transparent:	Ei
Lockable:	Ei
Eject-mechanism:	Ei
Insulated mounting:	Ei
With function lighting:	Ei
With orientation lighting:	Ei
Over voltage protection:	Ei
Fault current protection:	Ei
With miniature fuse:	Ei
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Lacquered
Surface finishing:	Matt
Anti-bacterial treatment:	Ei
With loop through function:	Ei

# Tuotekortti

Euro socket outlet, 3-gang, shuttered, screwless terminals, branching terminals, painted steel



With on/off switch:	Ei
Rotated central insert:	Ei
Frequency:	50 Hz
Device width:	71 mm
Device height:	35 mm
Device depth:	71 mm
Min. depth of built-in installation box:	23 mm