


Socket outlet

Euro socket outlet, 3-gang, shuttered, screwless terminals, branching terminals, black matt



Tyyppi: 303UC-885

Tuotekoodi: 2TKA00002907

GTIN: 6438199004631



3-gang Euro socket outlet with center plate. There are terminals for each contact of the socket outlet for max 4 rigid wires and 2 X-terminals for 2-rigid wires. The socket outlet insert without the cover plate is screen-protected.

Tekniset tiedot

Sähkösuureet

| | |
|------------------|-------|
| Nominal current: | 2.5 A |
| Nominal voltage: | 250 V |

Luokitus

| | |
|---|------|
| Suitable for degree of protection (IP): | IP21 |
|---|------|

Pakkaus

| | |
|----------|---------------|
| Paketti: | 1/10/100/1800 |
| Yksikkö: | kpl |

ETIM Data

| | |
|-----------------------------------|------------------------------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000125 |
| Model: | EURO plug (CEE 7/16) |
| Number of active pins (round): | 2 |
| With signal lamp: | Ei |
| Number of units: | 3 |
| Number of phases: | 1 |
| Imprint/indication: | None |
| Connection type: | Push-in clamp |
| With hinged lid: | Ei |
| With enhanced contact protection: | Kyllä |
| Label space/information surface: | Ei |
| Colour: | Black |
| RAL-number (similar): | 9005 |
| Metallic colour: | Ei |
| Transparent: | Ei |
| Lockable: | Ei |
| Eject-mechanism: | Ei |
| Insulated mounting: | Ei |
| With function lighting: | Ei |
| With orientation lighting: | Ei |
| Over voltage protection: | Ei |
| Fault current protection: | Ei |
| With miniature fuse: | Ei |
| Special power supply: | No special power supply |
| Mounting method: | Flush mounted (plaster) |
| Type of fastening: | Mounting with claw and screw |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Kyllä |
| Surface protection: | Lacquered |
| Surface finishing: | Matt |
| Anti-bacterial treatment: | Ei |

Tuotekortti

Euro socket outlet, 3-gang, shuttered, screwless terminals, branching terminals, black matt



| | |
|--|-------|
| With loop through function: | Ei |
| With on/off switch: | Ei |
| Rotated central insert: | Ei |
| Frequency: | 50 Hz |
| Device width: | 71 mm |
| Device height: | 35 mm |
| Device depth: | 71 mm |
| Min. depth of built-in installation box: | 23 mm |