

Switch

Universal switch, 1-fold

Tyyppi: FAK1021

Tuotekoodi: 2TKA00003792

GTIN: 6438199005218



Universal switch with one change over contact. Good marking possibilities. Nominal voltage of LED: 24 V ac/dc (operates 8 – 30 V ac/dc, brightness changes). Loading capacity of switch (max) 30 V ac / 35 V dc, 100 mA ac/dc, 3 VA / 3 W.

Tekniset tiedot

Sähkösuureet

Nominal voltage:	24 V
------------------	------

Luokitus

Suitable for degree of protection (IP):	IP20
---	------

Signal products

Loading capacity of switch (max):	30 Vac / 35 Vdc, 100 mA ac/dc
Operating voltage of signal lamp:	9,5 - 28 V ac / 9,5 - 35 V dc
Current drain of signal lamp:	10 mA ac / 10 mA dc

Pakkaus

Paketti:	1/10/100/1200
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000029
Assembly arrangement:	Basic element with full cover plate
Model:	Single push button
Method of operation:	Push button
Number of contacts as normally closed contact:	4
Number of contacts as change-over contact:	1
Contactless type:	Ei
Number of rockers:	1
Number of poles:	1
Rated current:	1 A
With lighting:	Ei
With light source:	Ei
With signal lamp:	Ei
Feedback-signal contact:	Kyllä
Connection type:	Screwed terminal
Mounting method:	Flush mounted (plaster)
Type of fastening:	Screw mounting
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Anti-bacterial treatment:	Ei
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	White
RAL-number (similar):	9010
Transparent:	Ei
Label space/information surface:	Kyllä
Imprint:	None
Impact strength:	IK00
Device width:	71 mm
Device height:	39 mm

Tuotekortti

Universal switch, 1-fold



Device depth:	71 mm
Min. depth of built-in installation box:	21 mm
Compatible with Apple HomeKit:	Ei
Compatible with Google Assistant:	Ei
Compatible with Amazon Alexa:	Ei
IFTTT support available:	Ei