

Tuotekortti

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, matt black



Socket outlet

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, matt black



Tyyppi: 302EUJT-885

Tuotekoodi: 2TKA00003863

GTIN: 6438199005348



There are terminals for each contact of the socket outlet for max 4 rigid wires. The socket outlet insert without the cover plate is screen-protected. Very flat construction. Installation in special 1,5X mounting box.

Tekniset tiedot

Sähkösuureet

| | |
|------------------|-------|
| Nominal current: | 16 A |
| Nominal voltage: | 250 V |

Luokitus

| | |
|-----------------------------------------|------|
| Suitable for degree of protection (IP): | IP21 |
|-----------------------------------------|------|

Pakkaus

| | |
|----------|---------------|
| Paketti: | 1/10/100/1200 |
| Yksikkö: | kpl |

ETIM Data

© ABB 2026

Y-tunnus 0763403-0

www.installationmaterials.com

Asiakaspalvelukeskus

puh. 010 222 1999

contact.center@fi.abb.com

Puhelinvaihte

010 22 11

Tuotekortti

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, matt black



| | |
|------------------------------------|-----------------------------|
| ETIM Version: | ETIM-8.0 |
| ETIM Class: | EC000125 |
| Model: | Protective contact (type F) |
| Protective contact: | Kyllä |
| Protective earth pin round: | Ei |
| With signal lamp: | Ei |
| With built-in USB power supply: | Ei |
| Number of units: | 2 |
| Number of modules (module system): | 1 |
| Number of phases: | 1 |
| Connection type: | Push-in clamp |
| With hinged lid: | Ei |
| With enhanced contact protection: | Kyllä |
| Label space/information surface: | Ei |
| Colour: | Black |
| RAL-number (similar): | 9005 |
| Metallic colour: | Ei |
| Transparent: | Ei |
| Lockable: | Ei |
| Eject-mechanism: | Ei |
| Insulated mounting: | Kyllä |
| With function lighting: | Ei |
| With orientation lighting: | Ei |
| Over voltage protection: | Ei |
| Fault current protection: | Ei |
| With miniature fuse: | Ei |
| Special power supply: | No special power supply |
| Mounting method: | Flush mounted (plaster) |
| Type of fastening: | Mounting with screw |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Kyllä |
| Surface protection: | Lacquered |

Tuotekortti

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, matt black



| | |
|------------------------------------------|--------|
| Surface finishing: | Matt |
| Anti-bacterial treatment: | Ei |
| With on/off switch: | Ei |
| With loop through function: | Ei |
| Rotated central insert: | Ei |
| Frequency: | 50 Hz |
| Device width: | 120 mm |
| Device height: | 80 mm |
| Device depth: | 40 mm |
| Min. depth of built-in installation box: | 17 mm |