

# Junction box IP65

Surface-mounted junction box, IP65, 104 x 104mm, black



**Tyyppi:** AP10M

**Tuotekoodi:** 2TKA00004261

**GTIN:** 6438199008158



**IP65**



The black square junction box AP10M (6,0 mm<sup>2</sup>, 500 V) is equipped with 12 membrane cable entries (Ø 19 mm) in the sides, and two on the bottom. Cables are easy to connect by simply inserting the stripped ends through the inlets. The box locks by snapping and can be opened by inserting a screwdriver (for example) into the opening slots - no screws are needed. The box can be furnished with strain-reliefs AS9.10, AS9, AS9.1 and AS9.3. Mounting temperature -25...+60 °C. Made of halogen free material (IEC/61249-2-21)

## Tekniset tiedot

### Sähkösuureet

Rated voltage:	500 V
Wire range:	6 mm <sup>2</sup>

### Luokitus

Enclosure class:	IP65
------------------	------

## Dimensions

Dimensions:	104 x 104 mm
-------------	--------------

## Thermal conditions

Operating temperature:	-25 ... 60 °C
------------------------	---------------

## Colors

Colour:	Black
Colour code:	RAL9003

## Pakkaus

Paketti:	5/30
Yksikkö:	kpl

## ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002600
Model:	Junction box
Equipped with:	None
Shape:	Square
Mounting method:	Universal
Mounting in the soil:	Ei
Mounting under water:	Ei
For tube diameter:	19 mm
Inlet from the rear:	Kyllä
Length:	48 mm
Width:	104 mm
Depth:	104 mm
Tackable:	Ei
Number of inlets:	14
Type of housing feed-through:	Seal membrane
Material:	Plastic

# Tuotekortti

Surface-mounted junction box, IP65, 104 x 104mm, black



Halogen free:	Kyllä
Surface protection:	Untreated
Colour:	Black
Degree of protection (IP):	IP65
Cover model:	Blind cover
Transparent cover:	Ei
Cover attachment:	Snapped on
Castable:	Ei
With casting compound:	Ei
Sealable:	Kyllä
Rated insulation voltage Ui:	500 V
With screening:	Ei
Weatherproof:	Kyllä
Operating temperature:	-25...60 °C
Explosion-tested version:	Ei