

## Tuotekortti

Socket outlet, Impressivo, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, black matt, IP44



# Socket outlet

Socket outlet, Impressivo, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, black matt, IP44



**Tyyppi:** 302EUJW-885

**Tuotekoodi:** 2TKA00004463

**GTIN:** 6438199008615



There are terminals for each contact of the socket outlet for max 4 rigid wires. No X-terminals. The socket outlet insert without the cover plate is screen-protected.

## Tekniset tiedot

### Sähkösuureet

Nominal current:	16 A
Nominal voltage:	250 V

### Luokitus

Suitable for degree of protection (IP):	IP44
---	------

### Pakkaus

Paketti:	1/10/100/1200
Yksikkö:	kpl

### ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

# Tuotekortti

Socket outlet, Impressivo, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, black matt, IP44



ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	Ei
Number of units:	2
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Ei
With enhanced contact protection:	Kyllä
Label space/information surface:	Ei
Colour:	Black
RAL-number (similar):	9005
Metallic colour:	Ei
Transparent:	Ei
Lockable:	Ei
Eject-mechanism:	Ei
Insulated mounting:	Ei
With function lighting:	Ei
With orientation lighting:	Ei
Over voltage protection:	Ei
Fault current protection:	Ei
With miniature fuse:	Ei
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Lacquered
Surface finishing:	Matt
Anti-bacterial treatment:	Ei
With loop through function:	Ei
With on/off switch:	Ei

# Tuotekortti

Socket outlet, Impressivo, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, black matt, IP44



Rotated central insert:	Ei
Frequency:	50 Hz
Device width:	100 mm
Device height:	85 mm
Device depth:	48 mm
Min. depth of built-in installation box:	17 mm