

Lighting outlet

DCL lighting outlet, ceiling outlet, flush mounting, black

Tyyppi: AKK14M

Tuotekoodi: 2TKA00004539

GTIN: 6438199008776



Ceiling rose AKK14 is an earthed, bipolar class 1 black ceiling rose. AKK14 crown cover can be mounted onto the junction box. The group cables, 2,5 mm² (-o-), may be continued. Each ceiling rose can carry a max. 6 A 250 V lighting appliance up to the weight of 15 kilos.



Tekniset tiedot

Sähkösuureet

Nominal current:	6 A
Nominal voltage:	250 V

Luokitus

Suitable for degree of protection (IP):	IP20
---	------

Dimensions

Height:	70 mm
---------	-------

Pakkaus

Paketti:	4/40
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Model:	DCL
With signal lamp:	Ei
Number of units:	1
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
With hinged lid:	Ei
With enhanced contact protection:	Ei
Label space/information surface:	Ei
Colour:	Black
RAL-number (similar):	9005
Metallic colour:	Ei
Transparent:	Ei
Lockable:	Ei
Eject-mechanism:	Ei
Insulated mounting:	Ei
With function lighting:	Ei
With orientation lighting:	Ei
Over voltage protection:	Ei
Fault current protection:	Ei
With miniature fuse:	Ei
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	Ei

Tuotekortti

DCL lighting outlet, ceiling outlet, flush mounting, black



With loop through function:	Ei
With on/off switch:	Ei
Rotated central insert:	Ei
Frequency:	50...60 Hz
Impact strength:	IK00
Device width:	115 mm
Device height:	70 mm
Device depth:	115 mm
Min. depth of built-in installation box:	31 mm
Compatible with Apple HomeKit:	Ei
Compatible with Amazon Alexa:	Ei
Compatible with Google Assistant:	Ei
IFTTT support available:	Ei
With Wi-Fi signal repeater:	Ei
With built-in bluetooth speaker:	Ei