

Mounting box

Height 68 mm, screw c/c distance 60 mm

Tyyppi: AUB60**Tuotekoodi:** 2TKA00004663**GTIN:** 6438199008851

Mounting box AUB60 is especially designed for off site and on site casting applications. Box height is 68 mm. Box has two inlets with locking springs for 20 or 25 mm conduits. Additional inlets can be attached to other sides without need of any tooling. The mounting box includes a rotating, steplessly adjustable extension ring. The extension ring can be tilted 0-4°. Box combinations can be created without additional accessories and box has large inside space. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (650 °C). Maximum number of conductors is 30 pcs.

Tekniset tiedot

Thermal conditions

Operating temperature:	-25 ... 90 °C
------------------------	---------------

Pakkaus

Paketti:	50
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601

Mounting method:	Concrete building
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Single
Provided with revolving ring:	Kyllä
Connectable:	Kyllä
Equipped with:	None
Diameter:	71 mm
Length:	167 mm
Width:	98 mm
Depth:	167 mm
Inner depth:	63 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Kyllä
Housing feed-through by break-out opening:	Kyllä
Housing feed-through by seal membrane:	Ei
Housing feed-through by nozzle:	Kyllä
Housing feed-through by step membrane:	Ei
For tube diameter:	20/25 mm
Pipe locking:	Kyllä
Pipe locking optional:	Ei
Inlet from the rear:	Ei
Number of inlets:	8
Number of included spouts:	2
Material:	Plastic
Halogen free:	Kyllä
Surface protection:	Untreated
Colour:	White
Degree of protection (IP):	IP3X
Cover model:	Construction protective cover
Transparent cover:	Ei
Cover attachment:	Snapped on
Sealable:	Ei

Tuotekortti

Height 68 mm, screw c/c distance 60 mm



With screening:	Ei
Air tight:	Ei
Clamp position fixed:	Ei
Luminaire hook mounting:	Ei
Special application:	None