

# AUD13-05

Prefabricated socket outlet unit Without imprint Protective contact (SCHUKO) with Hinged Lid Green - Impressivo



**Tyyppi:** AUD13-05

**Tuotekoodi:** 2TKA00005317

**GTIN:** 6438199013862

AUD13-05 Prefabricated socket outlet unit, 6-gang Schuko, green

## Tekniset tiedot

### Sähkösuureet

|                  |       |
|------------------|-------|
| Nominal current: | 16 A  |
| Nominal voltage: | 250 V |

### Luokitus

|   |      |
|---|------|
| Suitable for degree of protection (IP): | IP20 |
|---|------|

### ETIM Data

|                                      |               |
|--------------------------------------|---------------|
| ETIM Version:                        | ETIM-9.0      |
| ETIM Class:                          | EC000125      |
| Number of active pins (round):       | 2             |
| With signal lamp:                    | Ei            |
| Number of socket outlets switchable: | 1             |
| Number of phases:                    | 1             |
| Imprint/indication:                  | None          |
| Connection type:                     | Push-in clamp |
| With hinged lid:                     | Kyllä         |

# Tuotekortti

Prefabricated socket outlet unit Without imprint Protective contact (SCHUKO) with Hinged Lid  
Green - Impressivo



|                                   |                            |
|-----------------------------------|----------------------------|
| With enhanced contact protection: | Kyllä                      |
| Label space/information surface:  | Ei                         |
| Colour:                           | Green                      |
| RAL-number (similar):             | 6025                       |
| Metallic colour:                  | Ei                         |
| Transparent:                      | Ei                         |
| Lockable:                         | Ei                         |
| Eject-mechanism:                  | Ei                         |
| Insulated mounting:               | Ei                         |
| With function lighting:           | Ei                         |
| With orientation lighting:        | Ei                         |
| Over voltage protection:          | Ei                         |
| Fault current protection:         | Ei                         |
| With miniature fuse:              | Ei                         |
| Special power supply:             | No special power supply    |
| Mounting method:                  | Wall duct                  |
| Type of fastening:                | Snap mounting (engagement) |
| Material:                         | Plastic                    |
| Material quality:                 | Thermoplastic              |
| Halogen free:                     | Kyllä                      |
| Surface protection:               | Untreated                  |
| Surface finishing:                | Glossy                     |
| Anti-bacterial treatment:         | Ei                         |
| With loop through function:       | Ei                         |
| With on/off switch:               | Ei                         |
| Rotated central insert:           | Ei                         |
| Frequency:                        | 50 Hz                      |
| Device width:                     | 45 mm                      |
| Device height:                    | 85 mm                      |
| Device depth:                     | 350 mm                     |