

Switch

2-pole 1-gang 1-way switch, Jussi, 2 X-terminals, "1/0" symbol



Tyyppi: 1062U

Tuotekoodi: 2TKA000139G1

GTIN: 6410021060121



Switch with screwless terminals and rocker with clip-on fastening. The terminals are for max 2 rigid wires. X-terminals are for extending the wires.

Tekniset tiedot

Sähkösuureet

| | |
|------------------|-------|
| Nominal voltage: | 250 V |
| Rated current: | 16 AX |

Luokitus

| | |
|---|------|
| Suitable for degree of protection (IP): | IP21 |
| Protection class: | IP21 |

Pakkaus

| | |
|----------|--------|
| Paketti: | 10/100 |
| Yksikkö: | kpl |

ETIM Data

| | |
|---------------|----------|
| ETIM Version: | ETIM-9.0 |
|---------------|----------|

Tuotekortti

2-pole 1-gang 1-way switch, Jussi, 2 X-terminals, "1/0" symbol



| | |
|--|--|
| ETIM Class: | EC001590 |
| Wiring system: | Two-way switch |
| Method of operation: | Rocker/button |
| Assembly arrangement: | Basic element with central cover plate |
| Push button switch: | Ei |
| Number of rockers: | 1 |
| Mounting method: | Flush mounted (plaster) |
| Type of fastening: | Screw mounting |
| With mounting plate: | Ei |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Kyllä |
| Anti-bacterial treatment: | Ei |
| Surface protection: | Untreated |
| Surface finishing: | Matt |
| Colour: | White |
| RAL-number (similar): | 9010 |
| Label space/information surface: | No |
| Illumination: | Optional |
| Function lighting: | Control and orientation |
| Type of lighting: | LED exchangeable |
| Rated current: | 16 A |
| Switching current for fluorescent lamps: | 16 AX |
| Feedback-signal contact: | Ei |
| Connection type: | Other |
| Washing machine switch: | Ei |
| Device width: | 71 mm |
| Device height: | 34 mm |
| Device depth: | 71 mm |
| Built-in depth: | 17 mm |
| Min. depth of built-in installation box: | 17 mm |