

Center plate

Center plate, Impressivo, 2 x RJ45, blind covers, aluminum



Tyyppi: 1819-83

Tuotekoodi: 2TKA000607G1

GTIN: 6418677330506



Center plate for the RJ45 inserts 1819.xx. It is suitable for the 85mm cover frames and with the 2519-xx adapter also for the 100mm cover frames. Manufactured from a durable high quality plastic material. The surface is glossy and easy to keep clean. Cleaning with a mild, standard household detergent. Be careful when cleaning with a powerful dissolvent.

Tekniset tiedot

Luokitus

| | |
|---|------|
| Suitable for degree of protection (IP): | IP20 |
|---|------|

Pakkaus

| | |
|----------|---------------|
| Paketti: | 1/10/100/2800 |
|----------|---------------|

| | |
|----------|-----|
| Yksikkö: | kpl |
|----------|-----|

ETIM Data

| | |
|---------------|----------|
| ETIM Version: | ETIM-9.0 |
|---------------|----------|

| | |
|-------------|----------|
| ETIM Class: | EC000018 |
|-------------|----------|

| | |
|-----------------------|---------------------|
| Assembly arrangement: | Central cover plate |
|-----------------------|---------------------|

| | |
|--------------|--------------|
| Utilization: | Modular Jack |
|--------------|--------------|

| | |
|------------------------------------|-------------------------|
| Support ring: | Ei |
| With dust cover: | Kyllä |
| With hinged lid: | Ei |
| Outlet direction: | Straight |
| Imprintable label: | With indication plate |
| With imprint: | Ei |
| Mounting method: | Flush mounted (plaster) |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Kyllä |
| Anti-bacterial treatment: | Ei |
| Surface protection: | Lacquered |
| Surface finishing: | Matt |
| Colour: | Aluminium |
| RAL-number (similar): | 9006 |
| Transparent: | Ei |
| Type of fastening: | Mounting with screw |
| With buses/couplings: | Ei |
| Suitable for number of connectors: | 2 |
| With strain relief: | Ei |
| Shielded buses: | Ei |
| Shielded housing: | Ei |
| Luster terminal: | Ei |
| With lighting: | Ei |
| Impact strength: | IK00 |
| Device width: | 70 mm |
| Device height: | 70 mm |
| Device depth: | 30 mm |