

---

# Motion detector, Aqua 180, IP44

Motion detector, Aqua 180, IP44, Jussi

---

**Tyyppi:** 6401U/6800UW

**Tuotekoodi:** 2TKA001426G1

**GTIN:** 6410035150719



230 V, 10 A relay, IP44, for flush mounting. Detection area 180 degrees has been extended approximately 35 degrees downward. This enables e.g. the surveillance of a stairway from an upper platform. The detection range depends on the installation height; for more information, see the specifications. Adjustable lighting level 5 - 250 lux, switch-off delay 2 sec.-32 min. The sensor component is mounted with the supplied Torx screws. Operation temperature -25 to +55 oC.



## Tekniset tiedot

### Sähkösuureet

Rated voltage:	230 V
Power ratio (cos φ):	0.5 ... 1
Switching current:	≤ 10 A

### Dimensions

Weight:	199 g
---------	-------

### Thermal conditions

Operating temperature:	-25 ... 55 °C
------------------------	---------------

## Colors

Colour:	White
---------	-------

## Electronics

Operating frequency:	50 Hz
Detection area:	Vaaka: 180°, pysty: 0-35°. Eteenpäin 10-15m, sivuille 2,5-5m
Switching time:	2s - 30 min, 1 s pulssi
Twilight switch:	5 ... 1000 Lux

## Pakkaus

Paketti:	1/10
Yksikkö:	kpl

## ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000138
Constant light control:	Ei
HVAC-control:	Ei
Networkable:	Ei
Suitable for wireless transmission:	Ei
Creep-under protection:	Ei
Response value sensitivity adjustable:	Ei
Response value luminosity adjustable:	Ei
Teach-function for response value luminosity:	Ei
Dim function with dimmer basic element:	Ei
Animal zone:	Ei
Staircase monitoring:	Ei
Halogen free:	Ei
Operation mode switch:	Ei
Switch-off delay self-learning:	Ei