

# Ceiling rose cover

Surface mounted ceiling rose with a lighting plug socket, earthed, bipolar, class 1, IP20



**Tyyppi:** AKK13

**Tuotekoodi:** 2TKA001667G1

**GTIN:** 6410011525128



Ceiling rose AKK13 is an earthed, bipolar class 1 ceiling rose. AKK13 crown cover can be mounted directly onto the ceiling or, in surface mounting, onto the junction box. The group cables, 2,5 mm<sup>2</sup> (-o-), may be continued. Each ceiling rose can carry a max. 6 A 250 V lighting appliance up to the weight of 15 kilos. The hook in the ceiling rose is released when the cover is opened. Smallest compatible conductor size 1.5 mm<sup>2</sup>.

## Tekniset tiedot

### Sähkösuureet

Nominal current:	6 A
Nominal voltage:	250 V

### Luokitus

Suitable for degree of protection (IP):	IP20
---	------

### Pakkaus

Paketti:	5/50
Yksikkö:	kpl

**ETIM Data**

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
With signal lamp:	Ei
Number of units:	1
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
With hinged lid:	Ei
With enhanced contact protection:	Ei
Label space/information surface:	Ei
Colour:	White
RAL-number (similar):	9010
Metallic colour:	Ei
Transparent:	Ei
Lockable:	Ei
Eject-mechanism:	Ei
Insulated mounting:	Ei
With function lighting:	Ei
With orientation lighting:	Ei
Over voltage protection:	Ei
Fault current protection:	Ei
With miniature fuse:	Ei
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	Ei
With loop through function:	Ei

# Tuotekortti

Surface mounted ceiling rose with a lighting plug socket, earthed, bipolar, class 1, IP20



With on/off switch:	Ei
Rotated central insert:	Ei
Frequency:	50...60 Hz
Impact strength:	IK00
Device width:	115 mm
Device height:	30 mm
Device depth:	115 mm