

# Ceiling rose cover

Ceiling rose, earthed, bipolar, IP20

**Tyyppi:** AKK13J

**Tuotekoodi:** 2TKA001668G1

**GTIN:** 6410011525135



The AKK13J lighting ceiling rose features screwless block technology, which makes installation faster and easier. Ceiling rose AKK13J (IP 20) is suitable for both flush and surface mounting. Smallest compatible conductor size 1.5 mm<sup>2</sup>.

## Tekniset tiedot

### Sähkösuureet

Nominal current:	6 A
Nominal voltage:	250 V

### Luokitus

Suitable for degree of protection (IP):	IP20
---	------

### Pakkaus

Paketti:	5/50
Yksikkö:	kpl

### ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125

With signal lamp:	Ei
Number of units:	1
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
With hinged lid:	Ei
With enhanced contact protection:	Ei
Label space/information surface:	Ei
Colour:	White
RAL-number (similar):	9010
Metallic colour:	Ei
Transparent:	Ei
Lockable:	Ei
Eject-mechanism:	Ei
Insulated mounting:	Ei
With function lighting:	Ei
With orientation lighting:	Ei
Over voltage protection:	Ei
Fault current protection:	Ei
With miniature fuse:	Ei
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	Ei
With loop through function:	Ei
With on/off switch:	Ei
Rotated central insert:	Ei
Frequency:	50...60 Hz

# Tuotekortti

Ceiling rose, earthed, bipolar, IP20



Impact strength:	IK00
Device width:	115 mm
Device height:	50 mm
Device depth:	115 mm
Min. depth of built-in installation box:	10 mm