

Auxiliary luminaire plug

Lighting plug socket for AKK13J



Tyyppi: AKL3

Tuotekoodi: 2TKA001680G1

GTIN: 6410011525326



Another lighting socket, AKL3, can be installed in the suspension tray, which facilitates the installation of an earthed chandelier light fitting.

Tekniset tiedot

Sähkösuureet

| | |
|------------------|-------|
| Nominal current: | 6 A |
| Nominal voltage: | 250 V |

Luokitus

| | |
|---|------|
| Suitable for degree of protection (IP): | IP20 |
|---|------|

Pakkaus

| | |
|----------|-------|
| Paketti: | 5/100 |
| Yksikkö: | kpl |

ETIM Data

| | |
|-------------------|----------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000125 |
| Model: | DCL |
| With signal lamp: | Ei |

| | |
|--------------------------------------|-------------------------|
| Number of units: | 1 |
| Number of socket outlets switchable: | 1 |
| Number of phases: | 1 |
| Imprint/indication: | None |
| With hinged lid: | Ei |
| With enhanced contact protection: | Ei |
| Label space/information surface: | Ei |
| Colour: | White |
| RAL-number (similar): | 9010 |
| Metallic colour: | Ei |
| Transparent: | Ei |
| Lockable: | Ei |
| Eject-mechanism: | Ei |
| Insulated mounting: | Ei |
| With function lighting: | Ei |
| With orientation lighting: | Ei |
| Over voltage protection: | Ei |
| Fault current protection: | Ei |
| With miniature fuse: | Ei |
| Special power supply: | No special power supply |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Kyllä |
| Surface protection: | Untreated |
| Surface finishing: | Matt |
| Anti-bacterial treatment: | Ei |
| With loop through function: | Ei |
| With on/off switch: | Ei |
| Rotated central insert: | Ei |
| Frequency: | 50...60 Hz |
| Impact strength: | IK00 |
| Device width: | 115 mm |
| Device height: | 17 mm |
| Device depth: | 115 mm |

Tuotekortti

Lighting plug socket for AKK13J



Min. depth of built-in installation box:

28 mm