

Alarm Unit

Alarm Unit, red

Tyyppi: FIM1200**Tuotekoodi:** 2TKA002131G1**GTIN:** 6410070607520

With red flashing light. Interrupting sound. Operating voltage: 9,5 - 28 V ac / 9,5 - 35 V dc. current consumption: 60 mA ac / 30 mA dc. Sound intensity / frequency: 78 dB / 2,3 kHz (intensity measured at a 30 cm distance). Sound disconnectable.

Tekniset tiedot

Sähkösuureet

| | |
|----------------------|-------------------------------|
| Operating voltage: | 9,5 - 28 V ac / 9,5 - 35 V dc |
| Current consumption: | 60 mA ac / 30 mA dc |

Luokitus

| | |
|------------------|------|
| Enclosure class: | IP20 |
|------------------|------|

Dimensions

| | |
|-------------|-------------|
| Dimensions: | 71x71x45 mm |
| Weight: | 40 g |

Thermal conditions

| | |
|------------------------|---------------|
| Operating temperature: | 5 ... 40 °C |
| Storage temperature: | -40 ... 70 °C |

Signal products

| | |
|------------------|---------|
| Sound frequency: | 2,3 kHz |
| Sound intensity: | ≤ 78 dB |

Pakkaus

| | |
|----------|---------------|
| Paketti: | 1/10/100/1200 |
| Yksikkö: | kpl |

ETIM Data

| | |
|----------------------------|-----------------------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC002247 |
| Model: | Room luminaire/buzzer |
| Colour: | White |
| RAL-number (similar): | 9010 |
| Voltage type: | AC/DC |
| With transformer: | Ei |
| Degree of protection (IP): | IP20 |
| Device width: | 71 mm |
| Device height: | 71 mm |
| Device depth: | 45 mm |