
Signal Panel

Tyyppi: FIM1300

Tuotekoodi: 2TKA002136G1

GTIN: 6410070607537



Could be used as an 3/6 points alarm receiving panel in calling and alarm systems. With 6 LED's. Good marking possibilities. Operating voltage: 12 - 24 V ac/dc. Current consumption/LED: 4 mA ac / 7 mA dc.

Tekniset tiedot

Luokitus

Enclosure class:	IP20
------------------	------

Dimensions

Dimensions:	71x71x35 mm
-------------	-------------

Weight:	40 g
---------	------

Thermal conditions

Operating temperature:	5 ... 40 °C
------------------------	-------------

Storage temperature:	-40 ... 70 °C
----------------------	---------------

Signal products

Operating voltage of signal lamp:	12 - 24 V ac/dc
-----------------------------------	-----------------

Current drain of signal lamp:	4 mA ac / 7 mA dc
-------------------------------	-------------------

Pakkaus

Paketti:	1/10/100/1200
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002247
Model:	Signalling set
Colour:	White
RAL-number (similar):	9010
Voltage type:	AC/DC
With transformer:	Ei
Degree of protection (IP):	IP20
Device width:	71 mm
Device height:	71 mm
Device depth:	35 mm