
Adapter Relay

Tyyppi: FIR2000

Tuotekoodi: 2TKA002155G1

GTIN: 6410070606158



The Adapter Relay is used to integrate the Office Signal System with calling- or alarm systems. Operating voltage 15 - 28 V ac.

Tekniset tiedot

Sähkösuureet

Nominal voltage:	24 V
Operating voltage:	15 - 28 V ac
Current consumption:	18 mA ac

Luokitus

Suitable for degree of protection (IP):	IP20
---	------

Dimensions

Dimensions:	71x71x35 mm
Weight:	35 g

Thermal conditions

Operating temperature:	5 ... 40 °C
Storage temperature:	-40 ... 70 °C

Signal products

Load capacity of contact:	1,0 A ac/dc, 42 V ac / 60 V dc, 30 VA / W
---------------------------	---

Pakkaus

Paketti:	1/10/100/1200
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000064
Assembly arrangement:	Other
With light source:	Ei
With flashlight:	Ei
With fixed symbol/imprint:	Ei
With exchangeable symbol:	Ei
Application as button:	No
Mounting method:	Flush mounted (plaster)
Type of fastening:	Screw mounting
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Kyllä
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	White
RAL-number (similar):	9010
Transparent:	Ei
Device width:	71 mm
Device height:	35 mm
Device depth:	71 mm
Min. depth of built-in installation box:	21 mm