

Pot.equalizer bar

Potential equalizer bar, max. 70 mm² Cu**Tyyppi:** AM4**Tuotekoodi:** 2TKA110004G1**GTIN:** 6410019130959

AM4 Potential equalizer bar is a busbar intended to connect different earthing conductors in buildings. AM4 is equipped with 10 pcs. of screw terminals of which two accept conductors up to 70 mm² and the rest are for conductors up to 50 mm². The bar is made out of tinned copper alloy, fitted with galvanized screws and tracking resistant spacers insulating bar from installation medium. Intended to be installed through holes (Ø 6,0 mm) in spacers to installation medium. Peeling length of conductors is 15 mm. Terminal screws are with hex 5 head and their tightening torque is 10,0 Nm



Tekniset tiedot

Pakkaus

Paketti:	5/50
Yksikkö:	kpl

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC001470
Model:	Without covering cap
Insulator:	Kyllä
Explosion-tested version:	Ei
Height:	173 mm

Tuotekortti

Potential equalizer bar, max. 70 mm² Cu



Width:	16 mm
Length:	37 mm
Number of connections round conductor 8 mm:	5
Number of connections round conductor 10 mm:	5
Number of connections round conductor 8-10 mm:	5
Material of contact rail:	Copper
Material of clamp:	Stainless steel V4A
Surface of the clamp:	Untreated