

# Junction box

**Tyyppi:** AU19

**Tuotekoodi:** 2TKA130027G1

**GTIN:** 6410011521199



The AU19 junction box has knock-outs for 8 inlets and 4 bottom inlets. The box can be fastened using side nailing or a PMR577 support. The box has four screw pillars, two for M4 screws and two for 3,5mm universal screws. The box is possible to install in cramped spaces. The depth, 47 mm, is the same as the depth of the mounting boxes. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C). Max amount of conductors 30pcs.

## Tekniset tiedot

### Pakkaus

Paketti:	100
Yksikkö:	kpl

### ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601
Mounting method:	Flush mounted (plaster)
Shape:	Round
Construction type:	Cable junction box
Model:	Single
Provided with revolving ring:	Ei
Connectable:	Kyllä

Equipped with:	None
Diameter:	94 mm
Length:	88 mm
Width:	88 mm
Depth:	88 mm
Inner depth:	45 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Kyllä
Housing feed-through by break-out opening:	Ei
Housing feed-through by seal membrane:	Ei
Housing feed-through by nozzle:	Ei
Housing feed-through by step membrane:	Ei
For tube diameter:	20/25 mm
Pipe locking:	Kyllä
Pipe locking optional:	Ei
Inlet from the rear:	Kyllä
Material:	Plastic
Halogen free:	Kyllä
Surface protection:	Untreated
Colour:	White
Degree of protection (IP):	IP44
Transparent cover:	Ei
Cover attachment:	Snapped on
Sealable:	Ei
With screening:	Ei
Air tight:	Ei
Clamp position fixed:	Ei
Luminaire hook mounting:	Ei
Special application:	None