

# Junction box

**Tyyppi:** AU8

**Tuotekoodi:** 2TKA130033G1

**GTIN:** 6410011521083



The AU8 junction box is 53 mm high and has eight inlets for  $\varnothing 20$  conduits. The box also has knock-outs for 4 side inlets and 4 bottom inlets. In wall installation the box can be attached with a AS13.12 support. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C). Max amount of conductors 30.

## Tekniset tiedot

### Pakkaus

Paketti:	100
Yksikkö:	kpl

### ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601
Mounting method:	Flush mounted (plaster)
Shape:	Round
Construction type:	Cable junction box
Model:	Single
Provided with revolving ring:	Ei
Connectable:	Ei
Equipped with:	None
Diameter:	94 mm

Length:	135 mm
Width:	135 mm
Depth:	135 mm
Inner depth:	49 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Ei
Housing feed-through by break-out opening:	Kyllä
Housing feed-through by seal membrane:	Ei
Housing feed-through by nozzle:	Kyllä
Housing feed-through by step membrane:	Ei
For tube diameter:	20/25 mm
Pipe locking:	Kyllä
Pipe locking optional:	Ei
Inlet from the rear:	Kyllä
Number of inlets:	8
Number of included spouts:	8
Material:	Plastic
Halogen free:	Kyllä
Surface protection:	Untreated
Colour:	White
Degree of protection (IP):	IP3X
Transparent cover:	Ei
Cover attachment:	Snapped on
Sealable:	Ei
With screening:	Ei
Air tight:	Ei
Clamp position fixed:	Ei
Luminaire hook mounting:	Ei
Special application:	None