

Center plate


Center plate, blind, steel

Type: 1742-866

Product ID: 2CKA001710A3751

GTIN: 4011395086742

 ϵ



Technical specification

Classification

|--|

Packing

Package:	1/10/100/1800
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000018
Assembly arrangement:	Basic element with central cover plate
Utilization:	Blind cap
Support ring:	Yes
With dust cover:	No

© ABB 2025

Business ID 0763403-0 www.installationmaterials.com **Customer service** puh. +358 10 222 1999

contact.center@fi.abb.com

ABB Exchange

Product Card

Center plate, blind, steel



Outlet direction: Bottom Imprintable label: without indication field With imprint: No Mounting method: Flush mounted (plaster) Material: Metal Material quality: Stainless steel Halogen free: Yes Anti-bacterial treatment: No Surface protection: Untreated Surface finishing: Matt Colour: Stainless steel Transparent: No Type of fastening: Mounting with claw and screw With buses/couplings: No With strain relief: No Shielded buses: No Shielded busing: No Shielded housing: No Uttle treminal: No With lighting: No Device width: 7 inm Device height: 7 inm Device depth: 41.6 mm Min. depth of bull-in installation box: 32 mm	With hinged lid:	No
With imprint:NoMounting method:Flush mounted (plaster)Material:MetalMaterial quality:Stainless steelHalogen free:YesAnti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:Stainless steelTransparent:NoType of fastening:Mounting with claw and screwNumber of modules (module system):1With buses/couplings:NoWith strain relief:NoShielded bousing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Outlet direction:	Bottom
Mounting method:Flush mounted (plaster)Material:MetalMaterial quality:Stainless steelHalogen free:YesAnti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:Stainless steelTransparent:NoType of fastening:Mounting with claw and screwNumber of modules (module system):1With buses/couplings:NoWith strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Imprintable label:	Without indication field
Material:MetalMaterial quality:Stainless steelHalogen free:YesAnti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:Stainless steelTransparent:NoType of fastening:Mounting with claw and screwNumber of modules (module system):1With buses/couplings:NoWith strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	With imprint:	No
Material quality:Stainless steelHalogen free:YesAnti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:Stainless steelTransparent:NoType of fastening:Mounting with claw and screwNumber of modules (module system):1With buses/couplings:NoWith strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Mounting method:	Flush mounted (plaster)
Halogen free: Anti-bacterial treatment: No Surface protection: Untreated Surface finishing: Matt Colour: Stainless steel Transparent: No Type of fastening: Mounting with claw and screw Number of modules (module system): I With buses/couplings: No With strain relief: No Shielded buses: No Shielded housing: No Untreated Mounting with claw and screw No Untreated No Un	Material:	Metal
Anti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:Stainless steelTransparent:NoType of fastening:Mounting with claw and screwNumber of modules (module system):1With buses/couplings:NoWith strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Material quality:	Stainless steel
Surface protection:UntreatedSurface finishing:MattColour:Stainless steelTransparent:NoType of fastening:Mounting with claw and screwNumber of modules (module system):1With buses/couplings:NoWith strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice depth:41.6 mm	Halogen free:	Yes
Surface finishing:MattColour:Stainless steelTransparent:NoType of fastening:Mounting with claw and screwNumber of modules (module system):1With buses/couplings:NoWith strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Anti-bacterial treatment:	No
Colour:Stainless steelTransparent:NoType of fastening:Mounting with claw and screwNumber of modules (module system):1With buses/couplings:NoWith strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Surface protection:	Untreated
Transparent: No Type of fastening: Mounting with claw and screw Number of modules (module system): 1 With buses/couplings: No With strain relief: No Shielded buses: No Shielded housing: No Luster terminal: No With lighting: No Device width: 71 mm Device depth: 41.6 mm	Surface finishing:	Matt
Type of fastening: Mounting with claw and screw Number of modules (module system): 1 With buses/couplings: No With strain relief: No Shielded buses: No Shielded housing: No Luster terminal: No With lighting: No Device width: 71 mm Device height: 71 mm Device depth: 41.6 mm	Colour:	Stainless steel
Number of modules (module system):1With buses/couplings:NoWith strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Transparent:	No
With buses/couplings:NoWith strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Type of fastening:	Mounting with claw and screw
With strain relief:NoShielded buses:NoShielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Number of modules (module system):	1
Shielded buses: Shielded housing: Luster terminal: With lighting: Device width: T1 mm Device height: T2 mm T2 mm T3 mm T4 mm T4 mm T5 mm	With buses/couplings:	No
Shielded housing:NoLuster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	With strain relief:	No
Luster terminal:NoWith lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Shielded buses:	No
With lighting:NoDevice width:71 mmDevice height:71 mmDevice depth:41.6 mm	Shielded housing:	No
Device width: 71 mm Device height: 71 mm Device depth: 41.6 mm	Luster terminal:	No
Device height: 71 mm Device depth: 41.6 mm	With lighting:	No
Device depth: 41.6 mm	Device width:	71 mm
	Device height:	71 mm
Min. depth of built-in installation box: 32 mm	Device depth:	41.6 mm
	Min. depth of built-in installation box:	32 mm