

# LED dim. insert flex, 1 g

**Type:** 64851 U-500

**Product ID:** 2CKA006500A0013

**GTIN:** 4011395294208



## Technical specification

### Packing

Package:	1/10
Unit:	PCS

### ETIM Data

Method of operation:	Push button
App control via Bluetooth:	No
Dimming phase cut-on:	Yes
Dimming phase cut-off:	Yes
Serial dimmer:	No
Type of load:	Universal and LED Retrofit
Substation input:	Yes
Light value memory:	Yes
Applicable with button:	Yes
Applicable with movement sensor:	Yes
Applicable with presence indicator:	Yes
Applicable with time switch/timer:	Yes
Applicable with transmission button:	Yes
Applicable with infrared button:	No

# Product Card

LED dim. insert flex, 1 g



Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	Black
Transparent:	No
Suitable for degree of protection (IP):	IP20
Impact strength:	IK00
Nominal voltage:	230 V
Control voltage:	220...240 V
Connection type:	Screwed terminal
Device width:	71 mm
Device height:	71 mm
Device depth:	30 mm
Min. depth of built-in installation box:	28 mm
Compatible with Apple HomeKit:	No
Compatible with Google Assistant:	No
Compatible with Amazon Alexa:	No
IFTTT support available:	No