# Dimmer

## DALI potentiometer insert




**Type:** 2117 U-500

**Product ID:** 2CKA006599A2987

**GTIN:** 4011395152218

CE

For DALI broadcast service (via central telegram).
For switching and dimming up to 64 DALI- devices like electronic ballasts and transformers with DALI-interface.
With rotary control and ON/OFF push operation.
Fool proved.
Brightness power-on level and backround brightness level adjustable, buffered.
With integrated LED illumination for orientation.
Color of orientation light adjustable (18 presets and OFF).
Up to 5 potentiometers are connectable in parallel.
Max. current consumption: 15 mA.
Not suitable in combination with other DALI-sensors.
An additional DALI power supply is needed, e.g. by Tridonic, Philips, Helvar or 2117/11 U.
Max. DALI-cable length: 300 m (1, 5 - 2, 5 $mm^2$).
Without cover plate.
Protection class (Device): IP 20
Temperature range (Device): 0 °C to 35 °C

# Technical specification

### Packing

| | |
|---|---|
| Package: | 1/10 |
| Unit: | PCS |

**© ABB 2026**
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11

## ETIM Data

| | |
|---|---|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000534 |
| Mounting method: | Flush mounted (plaster) |
| Control current: | 15 mA |
| Substation input: | Yes |
| Light value memory: | Yes |
| Min. depth of built-in installation box: | 28.5 mm |
| Device width: | 71 mm |
| Device height: | 71 mm |
| Device depth: | 51 mm |
| Metallic colour: | No |
| Compatible with Apple HomeKit: | No |
| Compatible with Google Assistant: | No |
| Compatible with Amazon Alexa: | No |
| IFTTT support available: | No |

**© ABB 2026**
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11