Automatic controller for light controlling system



Cover Plates (partly incl. Insert) - Saga

Type: 64761-UC-916-510

Product ID: 2CKA006800A3103

GTIN: 4011395321577

IP20

Movement detector sensor with measurement of ambient light. For automatic switching of devices dependent on motion and brightness. ./. Compatible with all free@home flex inserts. Adjusting elements on rear side. Extension of the detection range by means of master/slave combination. With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Surveillance density: 14 sectors with 56 switching segments. Switch-off delay: approx. 10 sec - 30 min or short-time pulse 1 sec adjustable.

Technical specification

Packing

Package:	1/1
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000133
Model:	Movement sensor
Sensor type:	Other
Scan angle:	180 °

© ABB 2026

Business ID 0763403-0
www.installationmaterials.com

Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

ABB Exchange
+358 10 22 11

Optimum mounting height:	1.1 m
Connection type:	Screwed terminal
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	No
Surface protection:	Untreated
Surface finishing:	Glossy
Anti-bacterial treatment:	No
Colour:	White
RAL-number (similar):	9003
Degree of protection (IP):	IP20
Voltage type:	AC
Frequency:	50 Hz
Nominal voltage:	230 V
Min. switch-on time:	10 s
Max. duty cycle:	30 min
Response value luminosity:	5...500 lx
Number of switching zones:	14
Width:	71 mm
Height:	71 mm
Depth:	52.6 mm
Built-in depth:	25 mm
Min. depth of built-in installation box:	25 mm
Compatible with Apple HomeKit:	No
Compatible with Google Assistant:	No
Compatible with Amazon Alexa:	No
IFTTT support available:	No

© ABB 2026
Business ID 0763403-0
www.installationmaterials.com

Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

ABB Exchange
+358 10 22 11