# Automatic controller for light controlling system



## Cover Plates (partly incl. Insert) Movement sensor - Saga

**Type:** 64765-UC-916-510

**Product ID:** 2CKA006800A3106

**GTIN:** 4011395321607

IP20

movement detector push-button switch combination

# Technical specification

### Packing

| | |
|---|---|
| Package: | 1/1 |
| Unit: | PCS |

### ETIM Data

| | |
|---|---|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000133 |
| Model: | Movement sensor |
| Sensor type: | Other |
| Scan angle: | 170 ° |
| Optimum mounting height: | 1.1 m |
| Mounting method: | Flush mounted (plaster) |
| Connection type: | Screwed terminal |
| Material: | Plastic |

© ABB 2026
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11

| | |
|---|---|
| Material quality: | Thermoplastic |
| Halogen free: | No |
| Surface protection: | Untreated |
| Surface finishing: | Glossy |
| Anti-bacterial treatment: | No |
| Colour: | White |
| RAL-number (similar): | 9003 |
| Degree of protection (IP): | IP20 |
| Voltage type: | AC |
| Frequency: | 50 Hz |
| Nominal voltage: | 230 V |
| Min. switch-on time: | 60 s |
| Max. duty cycle: | 10 min |
| Detection angle horizontal: | 0...170 ° |
| Response value luminosity: | 5...500 lx |
| Width: | 71 mm |
| Height: | 71 mm |
| Depth: | 63.77 mm |
| Built-in depth: | 25 mm |
| Min. depth of built-in installation box: | 25 mm |
| Compatible with Apple HomeKit: | No |
| Compatible with Google Assistant: | No |
| Compatible with Amazon Alexa: | No |
| IFTTT support available: | No |

**© ABB 2026**
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11