Socket outlet

Socket outlet, Impressivo, Schuko, 1-gang, screwless terminals, aluminum

Type: 20EUCK-83

Product ID: 2TKA00000437

GTIN: 6438199001470

There are terminals for each contact of the socket outlet. No 2 X-terminals. The terminals are for max 2 rigid wires.

Technical specification

Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

Classification

Suitable for degree of protection (IP):	IP21

Packing

Package:	1/10/100/1800
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Number of active pins (round):	2

—
© ABB 2026
Business ID 0763403-0
www.installationmaterials.com

—
Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

—
ABB Exchange
+358 10 22 11

Page 1 of 3

With signal lamp:	No
Number of units:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	Aluminium
RAL-number (similar):	9006
Metallic colour:	Yes
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Lacquered
Surface finishing:	Matt
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No
Frequency:	50 Hz
Device width:	71 mm

—

© ABB 2026

Business ID 0763403-0

www.installationmaterials.com

—

Customer service

puh. +358 10 222 1999

contact.center@fi.abb.com

—

ABB Exchange

+358 10 22 11

Page 2 of 3

Device height:	45 mm
Device depth:	71 mm
Min. depth of built-in installation box:	28 mm

—

Customer service

puh. +358 10 222 1999

contact.center@fi.abb.com

—

ABB Exchange

+358 10 22 11