

## Product Card

Socket outlet, ProDuct, 2xShuko, white



# Socket outlet

Socket outlet, ProDuct, 2xShuko, white

**Type:** AUD10-214

**Product ID:** 2TKA00000809

**GTIN:** 6438199002019



The socket-outlet is approved for extending a branch circuit with solid and rigid wires. When chaining several AUD10-socket-outlets, the recommended length of intermediate cables is 120 mm. The end piece package AUD30 or AUD31 is required for each socket group. The depth of box is 45 mm.

## Technical specification

### Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

### Classification

Suitable for degree of protection (IP):	IP20
---	------

### Packing

Package:	10/100
Unit:	PCS

### ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

# Product Card

Socket outlet, ProDuct, 2xShuko, white



ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	No
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9010
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Wall duct
Type of fastening:	Snap mounting (engagement)
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No

# Product Card

Socket outlet, ProDuct, 2xShuko, white



---

Frequency:	50 Hz
Device width:	45 mm
Device height:	85 mm
Device depth:	80 mm

---