

## Product Card

Socket outlet unit, ProDuct, 6xShuko, "DATA" label, white



# Socket outlet unit

Socket outlet unit, ProDuct, 6xShuko, "DATA" label, white



**Type:** AUD13-214D

**Product ID:** 2TKA00000823

**GTIN:** 6438199002156



Ready-to-install 2-gang socket outlet that contains an end package, covers, a junction box with strain-reliefs and a 3 connectors. Approved for 3-phase linking.

## Technical specification

### Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

### Classification

Suitable for degree of protection (IP):	IP20
---	------

### Dimensions

Dimensions:	345x85x45 mm
-------------	--------------

### Packing

Package:	1/25
Unit:	PCS

# Product Card

Socket outlet unit, ProDuct, 6xShuko, "DATA" label, white



## ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	No
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9010
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Wall duct
Type of fastening:	Snap mounting (engagement)
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt

# Product Card

Socket outlet unit, ProDuct, 6xShuko, "DATA" label, white



Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No
Frequency:	50 Hz
Device width:	45 mm
Device height:	85 mm
Device depth:	350 mm