# Countdown timer

## Basic timer, Impressivo, aluminum




**Type:** T210-83

**Product ID:** 2TKA00000877

**GTIN:** 6438199002262

Fixed time options: 15min, 30min, 1h, 2h, 4h and 8h. Exchangeable labels with the time options to mark center plate with selected time. 230 VAC, 50Hz, 0 - 40C, IP21, 2-pole wiring. 10A resistiv load (2300W), 2AX-load (e.g. fluorescent lamp). Screw terminals max 2,5mm2. Signal light when active.

# Technical specification

### Electrical quantities

| | |
|---|---|
| Nominal voltage: | 230 V |
| Rated current: | 10 A |

### Classification

| | |
|---|---|
| Suitable for degree of protection (IP): | IP21 |
| Protection class: | IP21 |

### Thermal conditions

| | |
|---|---|
| Operating temperature: | 0 … 40 °C |

**© ABB 2026**

**Business ID** 0763403-0

**www.installationmaterials.com**

**Customer service**

puh. +358 10 222 1999

contact.center@fi.abb.com

**ABB Exchange**

+358 10 22 11

## Dimensions

| | |
|---|---|
| A: | 70 mm |
| B: | 70 mm |
| C: | 32 mm |
| Recessing dimensions: | 18 mm |

## Electronics

| | |
|---|---|
| Operating frequency: | 50 Hz |
| Conductor size max.: | 2,5 mm2 |

## Packing

| | |
|---|---|
| Package: | 1/10/100/1200 |
| Unit: | PCS |

## ETIM Data

| | |
|---|---|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC001594 |
| Assembly arrangement: | Basic element with central cover plate |
| Number of contacts as normally open contact: | 1 |
| Model: | Electronic |
| Time setting: | 15...480 min |
| Mounting method: | Flush mounted (plaster) |
| Type of fastening: | Mounting with screw |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Surface protection: | Untreated |
| Surface finishing: | Glossy |
| Colour: | Aluminium |
| RAL-number (similar): | 9006 |
| Transparent: | No |
| Shortest switching interval: | 15 min |
| Random generator: | No |

© ABB 2026
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11

| | |
|---|---|
| Astro program: | No |
| Substation input: | No |
| Rated current: | 10 A |
| With brightness sensor connection: | No |
| Max. power: | 2300 W |
| Compatible with Apple HomeKit: | No |
| Compatible with Google Assistant: | No |
| Compatible with Amazon Alexa: | No |
| IFTTT support available: | No |
| Built-in depth: | 18 mm |
| Min. depth of built-in installation box: | 18 mm |
| Device width: | 71 mm |
| Device height: | 34 mm |
| Device depth: | 71 mm |

**© ABB 2026**
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11