Button / Buzzer



Button / Buzzer, 1-fold

Type: FIP1011

Product ID: 2TKA00003793

GTIN: 6438199005225

IP20

A device including a push button as well as a buzzer. The LED of the push button and the buzzer operates in parallel. The buzzer can be cancelled with the push button. When cancelled the LED remains on till the alarm goes off. Good marking possibilities on the push button and the name plate. Operating voltage 9,5 - 28 Vac / 9,5 - 35 Vdc. Current consumption: 45 mA ac / 25 mA dc. Load capacity of the switch: 30 Vac / 35 Vdc, 100 mA ac/dc, 3 VA / 3 W.

Technical specification

Electrical quantities

Operating voltage:	9,5 - 28 V ac / 9,5 - 35 V dc
Current consumption:	45 mA ac / 25 mA dc

Signal products

Sound frequency:	400 Hz, 70 dB / 30 cm
Loading capacity of switch (max):	100 mA ac/dc, 30 V ac / 35 V dc

Packing

Package:	1/10/100/1200
Unit:	PCS

© ABB 2026

Business ID 0763403-0
www.installationmaterials.com

Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

ABB Exchange
+358 10 22 11

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002247
Colour:	White
RAL-number (similar):	9010
Degree of protection (IP):	IP20
Device width:	71 mm
Device height:	39 mm
Device depth:	71 mm

© ABB 2026
Business ID 0763403-0
www.installationmaterials.com

Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

ABB Exchange
+358 10 22 11