# Socket outlet



## Socket outlet, Impressivo, Schuko, 4-gang, shuttered, screwless terminals, black matt

**Type:** 404EA-885

**Product ID:** 2TKA00004462

**GTIN:** 6438199008608

There is 2 times 2-gang socket outlet inserts in one unit. The socket outlet inserts are internally connected. In one socket outlet insert there are terminals for each contact of the socket outlet for max 4 rigid wires. No X-terminals.

# Technical specification

### Electrical quantities

| | |
|---|---|
| Nominal current: | 16 A |
| Nominal voltage: | 250 V |

### Classification

| | |
|---|---|
| Suitable for degree of protection (IP): | IP21 |
| Protection class: | IP21 |

### Packing

| | |
|---|---|
| Package: | 1/20 |
| Unit: | PCS |

**© ABB 2026**

**Business ID** 0763403-0

**www.installationmaterials.com**

**Customer service**

puh. +358 10 222 1999

contact.center@fi.abb.com

**ABB Exchange**

+358 10 22 11

## ETIM Data

| | |
|---|---|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000125 |
| Number of active pins (round): | 2 |
| With signal lamp: | No |
| Number of socket outlets switchable: | 1 |
| Number of phases: | 1 |
| Imprint/indication: | None |
| Connection type: | Push-in clamp |
| With hinged lid: | No |
| With enhanced contact protection: | Yes |
| Label space/information surface: | No |
| Colour: | Black |
| RAL-number (similar): | 9005 |
| Metallic colour: | No |
| Transparent: | No |
| Lockable: | No |
| Eject-mechanism: | No |
| Insulated mounting: | No |
| With function lighting: | No |
| With orientation lighting: | No |
| Over voltage protection: | No |
| Fault current protection: | No |
| With miniature fuse: | No |
| Special power supply: | No special power supply |
| Mounting method: | Surface mounted (plaster) |
| Type of fastening: | Mounting with screw |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Yes |
| Surface protection: | Lacquered |
| Surface finishing: | Matt |
| Anti-bacterial treatment: | No |

**© ABB 2026**
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11

| | |
|---|---|
| With loop through function: | No |
| With on/off switch: | No |
| Rotated central insert: | No |
| Frequency: | 50 Hz |
| Device width: | 115 mm |
| Device height: | 100 mm |
| Device depth: | 42 mm |

© ABB 2026
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11