Switch

Switch Two-way switch White - Saga

Type: 1066UW-916

Product ID: 2TKA00005002

GTIN: 6438199011226

Switch with screwless terminals and rocker with screw fastening. The terminals are for max 2 rigid wires. Including switch insert, rocker, cover frame and the seals. The switch is IP44. Bio-circular plastics used in the frame and support.

Technical specification

Electrical quantities

Nominal voltage:	250 V

Classification

Suitable for degree of protection (IP):	IP44

Packing

Package:	1/10/100/1200
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC001590
Wiring system:	Two-way switch

© ABB 2026

Business ID 0763403-0

www.installationmaterials.com

Customer service

puh. +358 10 222 1999

contact.center@fi.abb.com

ABB Exchange

+358 10 22 11

Method of operation:	Rocker/button
Assembly arrangement:	Basic element with full cover plate
Push button switch:	No
Number of rockers:	1
Mounting method:	Flush mounted (plaster)
Type of fastening:	Screw mounting
With mounting plate:	No
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Anti-bacterial treatment:	No
Surface protection:	Untreated
Surface finishing:	Glossy
Colour:	White
RAL-number (similar):	9003
Label space/information surface:	No
Illumination:	Optional
Function lighting:	Control and orientation
Type of lighting:	LED exchangeable
Rated current:	16 A
Switching current for fluorescent lamps:	16 AX
Feedback-signal contact:	No
Connection type:	Other
Washing machine switch:	No
Device width:	85 mm
Device height:	39 mm
Device depth:	85 mm
Built-in depth:	17 mm
Min. depth of built-in installation box:	17 mm

© ABB 2026
Business ID 0763403-0
www.installationmaterials.com

Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

ABB Exchange
+358 10 22 11