

Junction box

AUB67M Junction box White IP3X

Type: AUB67M**Product ID:** 2TKA00005323**GTIN:** 6438199013916

Junction box AUB67M is especially designed for off site and on site casting applications. Box height is 96 mm. Box has several fixed inlets with locking springs to two directions (4 x 20 mm and 4 x 20/25 mm). The mounting box includes a rotating installation ring, has large inside space and removable back cover. Made of halogen free material (IEC/61249-2-21).

Technical specification

Packing

Package:	27/324
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601
Mounting method:	Concrete building
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Single
Provided with revolving ring:	Yes
Connectable:	Yes

Product Card

AUB67M Junction box White IP3X



Equipped with:	None
Diameter:	125 mm
Length:	200 mm
Width:	125 mm
Depth:	200 mm
Inner depth:	94 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Yes
Housing feed-through by break-out opening:	Yes
Housing feed-through by seal membrane:	No
Housing feed-through by nozzle:	Yes
Housing feed-through by step membrane:	No
For tube diameter:	20/25 mm
Pipe locking:	Yes
Pipe locking optional:	No
Inlet from the rear:	No
Number of inlets:	12
Number of included spouts:	8
Material:	Plastic
Halogen free:	Yes
Surface protection:	Untreated
Colour:	White
Degree of protection (IP):	IP3X
Cover model:	Construction protective cover
Transparent cover:	No
Cover attachment:	Snapped on
Sealable:	No
With screening:	No
Air tight:	No
Clamp position fixed:	No
Luminaire hook mounting:	No
Special application:	None