

Switch

1-gang 2-way switch, Jussi IP44, 2 Xterminals, lamp not included

Type: 1066SW

Product ID: 2TKA000192G1

GTIN: 6418677334559


















Technical specification

Electrical quantities

Nominal voltage:	250 V
Rated current:	16 AX

Classification

Packing

Package:	10/100
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC001590


© ABB 2025

Business ID 0763403-0

Customer service

puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange** +358 10 22 11

Product Card





Wiring system:	Two-way switch
Method of operation:	Rocker/button
Assembly arrangement:	Basic element with complete housing
Push button switch:	No
Number of rockers:	1
Mounting method:	Surface mounted (plaster)
Type of fastening:	Screw mounting
With mounting plate:	No
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Anti-bacterial treatment:	No
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	White
RAL-number (similar):	9010
Label space/information surface:	No
Illumination:	Optional
Function lighting:	Control and orientation
Type of lighting:	LED exchangeable
Rated current:	16 A
Switching current for fluorescent lamps:	16 AX
Feedback-signal contact:	No
Connection type:	Other
Washing machine switch:	No
Device width:	68 mm
Device height:	40 mm
Device depth:	80 mm
Built-in depth:	17 mm
Min. depth of built-in installation box:	17 mm

© ABB 2025
Business ID 0763403-0
www.installationmaterials.com

Customer service puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange** +358 10 22 11