

Switch

1-gang intermediate switch, Jussi IP44, 2 X-terminals, lamp not included

Type: 1067SW

Product ID: 2TKA000204G1

GTIN: 6418677334566


















Technical specification

Electrical quantities

Nominal voltage:	250 V
Rated current:	16 AX

Classification

Packing

Package:	1/10/100/1200
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC001590

© ABB 2025

Business ID 0763403-0

Customer service

puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange**

Product Card

1-gang intermediate switch, Jussi IP44, 2 X-terminals, lamp not included



Method of operation: Rocker/button Assembly arrangement: Basic element with complete housing Push button switch: No Number of rockers: 1 Mounting method: Surface mounted (plaster) Type of fastering: Screw mounting With mounting plate: No Material Plastic Material quality: Thermoplastic Material quality: Thermoplastic Anti-bacterial treatment: No Surface protection: Untreated Surface finishing: Matt Colour: White RAL-number (similar): 9016 Label space/information surface: No Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 A Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width:	Wiring system:	Intermediate switch
Push button switch: No Number of rockers: 1 Mounting method: Surface mounted (plaster) Type of fastening: Screw mounting With mounting plate: No Material: Plastic Material quality: Thermoplastic Halogen free: Yes Anti-bacterial treatment: No Surface protection: Untreated Surface finishing: Matt Colour: White RAL-number (similar): 9016 Label space/information surface: No Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device depth: 80 mm Bult-in depth: 17 mm	Method of operation:	Rocker/button
Number of rockers: 1 Mounting method: Surface mounted (plaster) Type of fastening: Screw mounting With mounting plate: No Material: Plastic Material quality: Thermoplastic Halogen free: Yes Anti-bacterial treatment: No Surface protection: Untreated Surface finishing: Matt Colour: White RAL-number (similar): 9016 Label space/information surface: No Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Device depth: 80 mm Bull-in depth: 17 mm	Assembly arrangement:	Basic element with complete housing
Mounting method:Surface mounted (plaster)Type of fastening:Screw mountingWith mounting plate:NoMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesAnti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:WhiteRAL-number (similar):9016Label space/information surface:NoIllumination:OptionalFunction lighting:Control and orientationType of lighting:LED exchangeableRated current:16 AXSwitching current for fluorescent lamps:16 AXFeedback-signal contact:NoConnection type:OtherWashing machine switch:NoDevice width:68 mmDevice height:40 mmDevice depth:80 mmBult-in depth:17 mm	Push button switch:	No
Type of fastening: Screw mounting With mounting plate: No Material: Plastic Material quality: Thermoplastic Halogen free: Yes Anti-bacterial treatment: No Surface protection: Untreated Surface finishing: Matt Colour: White RAL-number (similar): 9016 Label space/information surface: No Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Bullt-in depth: 17 mm	Number of rockers:	1
With mounting plate:NoMaterial:PlasticMaterial quality:ThermoplasticHalogen free:YesAnti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:WhiteRAL-number (similar):9016Label space/information surface:NoIllumination:OptionalFunction lighting:Control and orientationType of lighting:LED exchangeableRated current:16 ASwitching current for fluorescent lamps:16 AXFeedback-signal contact:NoConnection type:OtherWashing machine switch:NoDevice width:68 mmDevice beight:40 mmDevice depth:80 mmBull-in depth:17 mm	Mounting method:	Surface mounted (plaster)
Material:PlasticMaterial quality:ThermoplasticHalogen free:YesAnti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:WhiteRAL-number (similar):9016Label space/information surface:NoIllumination:OptionalFunction lighting:Control and orientationType of lighting:LED exchangeableRated current:16 AXSwitching current for fluorescent lamps:16 AXFeedback-signal contact:NoConnection type:OtherWashing machine switch:NoDevice width:68 mmDevice depth:40 mmBuilt-in depth:17 mm	Type of fastening:	Screw mounting
Material quality:ThermoplasticHalogen free:YesAnti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:WhiteRAL-number (similar):9016Label space/information surface:NoIllumination:OptionalFunction lighting:Control and orientationType of lighting:LED exchangeableRated current:16 ASwitching current for fluorescent lamps:16 AXFeedback-signal contact:NoConnection type:OtherWashing machine switch:NoDevice width:68 mmDevice height:40 mmDevice depth:80 mmBuilt-in depth:17 mm	With mounting plate:	No
Halogen free:YesAnti-bacterial treatment:NoSurface protection:UntreatedSurface finishing:MattColour:WhiteRAL-number (similar):9016Label space/information surface:NoIllumination:OptionalFunction lighting:Control and orientationType of lighting:LED exchangeableRated current:16 ASwitching current for fluorescent lamps:16 AXFeedback-signal contact:NoConnection type:OtherWashing machine switch:NoDevice width:68 mmDevice height:40 mmDevice depth:80 mmBuilt-in depth:17 mm	Material:	Plastic
Anti-bacterial treatment: Surface protection: Untreated Untreated Surface finishing: Matt Colour: White RAL-number (similar): 9016 Label space/information surface: No Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Device depth: 80 mm Built-in depth: 17 mm	Material quality:	Thermoplastic
Surface protection: Surface finishing: Matt Colour: White RAL-number (similar): 9016 Label space/information surface: No Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Device depth: 80 mm Built-in depth: 17 mm	Halogen free:	Yes
Surface finishing: Matt Colour: White RAL-number (similar): 9016 Label space/information surface: No Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Device depth: 80 mm Built-in depth: 17 mm	Anti-bacterial treatment:	No
Colour: White RAL-number (similar): 9016 Label space/information surface: No Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Built-in depth: 17 mm	Surface protection:	Untreated
RAL-number (similar): Label space/information surface: No Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Built-in depth: 17 mm	Surface finishing:	Matt
Label space/information surface: Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: Device height: 40 mm Device depth: 80 mm Built-in depth: 17 mm	Colour:	White
Illumination: Optional Function lighting: Control and orientation Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Device depth: 80 mm Built-in depth: 17 mm	RAL-number (similar):	9016
Function lighting: Type of lighting: LED exchangeable Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Device depth: 80 mm Built-in depth: 17 mm	Label space/information surface:	No
Type of lighting: Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Built-in depth: 17 mm	Illumination:	Optional
Rated current: 16 A Switching current for fluorescent lamps: 16 AX Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: 68 mm Device height: 40 mm Device depth: 80 mm Built-in depth: 17 mm	Function lighting:	Control and orientation
Switching current for fluorescent lamps: Feedback-signal contact: No Connection type: Other Washing machine switch: No Device width: Device height: Device depth: Built-in depth: 16 AX No No No No 16 AX No No 17 mm	Type of lighting:	LED exchangeable
Feedback-signal contact: Connection type: Other Washing machine switch: Device width: Device height: Device depth: Built-in depth: No Other No Other No 80 mm 17 mm	Rated current:	16 A
Connection type: Washing machine switch: Device width: Device height: Device depth: Built-in depth: Other No 0ther No 80 mm 17 mm	Switching current for fluorescent lamps:	16 AX
Washing machine switch:NoDevice width:68 mmDevice height:40 mmDevice depth:80 mmBuilt-in depth:17 mm	Feedback-signal contact:	No
Device width: 68 mm Device height: 40 mm Device depth: 80 mm Built-in depth: 17 mm	Connection type:	Other
Device height: 40 mm Device depth: 80 mm Built-in depth: 17 mm	Washing machine switch:	No
Device depth: 80 mm Built-in depth: 17 mm	Device width:	68 mm
Built-in depth: 17 mm	Device height:	40 mm
	Device depth:	80 mm
Min. depth of built-in installation box: 17 mm	Built-in depth:	17 mm
	Min. depth of built-in installation box:	17 mm

© ABB 2025
Business ID 0763403-0
www.installationmaterials.com

Customer service puh. +358 10 222 1999 contact.center@fi.abb.com **ABB Exchange** +358 10 22 11