

Socket outlet

Socket outlet, Jussi, Schuko, 2-gang, floor installation



Type: 302EUC1L

Product ID: 2TKA000941G1

GTIN: 6418677328534



There are terminals for each contact of the socket outlet for max 4 rigid wires. No X-terminals. The socket outlet insert without the cover plate is screen-protected.

Technical specification

Electrical quantities

Nominal current:	16 A
Nominal voltage:	250 V

Classification

Suitable for degree of protection (IP):	IP21
---	------

Packing

Package:	5/50
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125

Product Card

Socket outlet, Jussi, Schuko, 2-gang, floor installation



Number of active pins (round):	2
With signal lamp:	No
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	No
With enhanced contact protection:	Yes
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9010
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No
Frequency:	50 Hz

Product Card

Socket outlet, Jussi, Schuko, 2-gang, floor installation



Device width:	94 mm
Device height:	47 mm
Device depth:	123 mm
Min. depth of built-in installation box:	17 mm