# Mounting box

## for 12-13/24-26 mm board



**Type:** AU67

**Product ID:** 2TKA001746G1

**GTIN:** 6418677332340

The mounting box has a rotating ring for adjusting the screw holes for device installation in optimal angle and screw distance is c/c 67mm. The green adapter ring, delivered with the box, is used in single-board walls (12-13 mm). The ring is removed when the wall thickness is two boards (24-26 mm). There are five fixed inlets for 16 mm conduits, three are open, and two fixed inlets for 20 mm conduits. All inlets are equipped with a locking device in metal for reliable connection between the conduits (flexi or stiff pipe) and the box. In addition, there are two knock outs on the sides and two in the bottom for different inlets.

Manufactured from halogen free material (IEC/61249-2-21), the box complies with the IEC/EN60670:2005 glow wire test (850 °C).

# Technical specification

### Electrical quantities

| | |
|---|---|
| Rated voltage: | 400 V |

### Classification

| | |
|---|---|
| Enclosure class: | IP44 |

### Thermal conditions

| | |
|---|---|
| Operating temperature: | -25 … 60 °C |

© ABB 2026

**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11

## Certifications

| | |
|---|---|
| Approval: | SP SITAC 1002, SC0854-09 |

## Packing

| | |
|---|---|
| Package: | 40 |
| Unit: | PCS |

## ETIM Data

| | |
|---|---|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC002601 |
| Mounting method: | Flush mounted (plaster) |
| Shape: | Round |
| Construction type: | Other |
| Model: | Single |
| Provided with revolving ring: | Yes |
| Connectable: | Yes |
| Equipped with: | None |
| Diameter: | 90 mm |
| Length: | 90 mm |
| Width: | 130 mm |
| Depth: | 90 mm |
| Inner depth: | 53 mm |
| For number of electric fittings: | 1 |
| Mounting switching equipment: | Screwing |
| With screws: | Yes |
| Housing feed-through by break-out opening: | Yes |
| Housing feed-through by seal membrane: | No |
| Housing feed-through by nozzle: | Yes |
| Housing feed-through by step membrane: | No |
| For tube diameter: | 16/20 mm |
| Pipe locking: | Yes |
| Pipe locking optional: | No |
| Inlet from the rear: | Yes |

**© ABB 2026**
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11

| | |
|---|---|
| Number of inlets: | 7 |
| Number of included spouts: | 7 |
| Material: | Plastic |
| Halogen free: | Yes |
| Surface protection: | Untreated |
| Colour: | Blue |
| Degree of protection (IP): | IP44 |
| Cover model: | Construction protective cover |
| Transparent cover: | No |
| Cover attachment: | Snapped on |
| Sealable: | No |
| With screening: | No |
| Air tight: | No |
| Clamp position fixed: | No |
| Luminaire hook mounting: | No |
| Special application: | None |

**© ABB 2026**
**Business ID** 0763403-0
**www.installationmaterials.com**

**Customer service**
puh. +358 10 222 1999
contact.center@fi.abb.com

**ABB Exchange**
+358 10 22 11