Leak Guard

Type: FEH2100

Product ID: 2TKA002115G1

GTIN: 6410070607131

IP20

The Leak Guard unit operates as the standard Control Unit FEH1001, with the exception that the loop monitors leakage current (10 µA). Tape sensors, conduit pairs or other leakage sensors could be connected to the device. Memory/no memory function. Potential free output. Cancelling button with LED. Operating voltage: 9.5 - 28 V ac / 9.5 - 35 V dc. Current consumption: 75 mA ac / 40 mA dc. Good marking possibilities on the button and name plate.

Technical specification

Electrical quantities

Current consumption:	70 mA ac / 40 mA dc

Classification

Enclosure class:	IP20

Dimensions

Dimensions:	71x71x39 mm
Weight:	45 g

Thermal conditions

Operating temperature:	5 … 40 °C
Storage temperature:	-40 … 70 °C

© ABB 2026

Business ID 0763403-0

www.installationmaterials.com

Customer service

puh. +358 10 222 1999

contact.center@fi.abb.com

ABB Exchange

+358 10 22 11

Signal products

Load capacity of power supply:	1,0 A ac/dc, 30 VA / W
Load capacity of potential free contact:	1,0 A ac/dc, 42 V ac / 60 V dc, 30 VA / W
Alarm delay:	0,1 s (ei viiveen valintaa)
Loop's memory function:	on / off
Loop's action limit:	5 … 10 µA

Packing

Package:	1/10/100/1200
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC001764
Type of messaging:	Water
Mounting method:	Surface mounting
Indication:	Optic/acoustic
Operating voltage:	24 V
Colour:	White
Height:	71 mm
Width:	71 mm
Depth:	45 mm
Compatible with Apple HomeKit:	No
Compatible with Google Assistant:	No
Compatible with Amazon Alexa:	No
IFTTT support available:	No

© ABB 2026
Business ID 0763403-0
www.installationmaterials.com

Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

ABB Exchange
+358 10 22 11